

SPECIFICATION	update: 050105
---------------	----------------

Item Number	MONF812	Test Method
Name of Production	PE Cloth Protection Tape	

Structure (Composition)	Laminated PE Cloth
Backing Material	Acrylic Based Adhesive
Adhesive System	

Standard Size		
Thickness (mm)	0.16 ± 0.02 mm	JIS Z-0237
Width (mm)	50 ± 1.5 mm	JIS Z-0237
Length (M)	min. 25 M	JIS Z-0237

Physical Properties		
Adhesion Force (N/cm)	2.7 ± 0.7	JIS Z-0237
Ball Tack (No.) - J. Dow Method	19 ± 5	JIS Z-0237
Tensile Strength (N/cm)	min. 65	JIS Z-0237
Elongation (%)	min. 6	JIS Z-0237

Standard Color	Light Green
-----------------------	-------------

Packing	Width x Length	Rolls / Carton
	25mm x 25mm	60 rolls
	38mm x 25mm	36 rolls
	50mm x 25mm	30 rolls
	75mm x 25mm	18 rolls
	100mm x 25mm	12 rolls

Salient Feature
 No.812 is special designed for Nuclear Power Plant and Construction Industry during installation and maintenance. It's easy to tear by hand, high working efficiency is expected. No.812 had good weather resistance and moisture resistance. There is no adhesive residue problem after peel off the tape.

Warning
 Please remove dust, water, oil well before using and keep avoiding under the sunshine